



RHINOWASH

T +44 (0) 8708 600 600
F +44 (0) 1698 356 697
E info@rhinowash.com

Technical Specification Sheet

RHINO HR SERIES 12/20



Manual Hose Reel	Complete with wire braided high pressure hose available in various lengths to suit application with a 80m capacity a 10 metre (30ft) hose supplied as standard. Working pressure 400 bar (5800 psi) Bursting pressure 1000 bar (14500 psi)
Automatic Frost Protection	A heater is incorporated within the cabinet and is controlled by an internal frost-thermostat. When the temperature drops to 2°C the heater is automatically switched on to protect the internal equipment.
Chassis	A steel cabinet with lockable door for access into cabinet, powder coated to RAL3001. Allowing storage of lance and detergent (25lt)
Lance Holder	Attached to side of cabinet
Electric Controls	Option of remote start/stop control of the Pressure Washer from the Hose Reel Cabinet.
Mains Cable	Oil resistant and wire braided
Detergent Tank	25 litres / 5.5 gallons.
Voltage Versions	The 240v version is for connection to all Hot or Cold 12 Models The 415v version is for connection to all Hot or Cold 20/26 Models
Dimensions	585L x 756D x 1260H
Weight	87.6 Kg

Tech.Spec.AG.SATCAB.102904.001



Rhinowash Ltd a Scotkleen-Warwick Company, VAT No. 847308413 Company No. 272881
149A Glasgow Road, Wishaw, UK, ML2 7QJ
www.rhinowash.com

